



# Specification Sheet

Product:	Novara*
	
Fiber:	100% Polypropylene
Structure:	Loop pile: Level loop
Gauge:	1/10"
Stitches:	11 per inch
Tufts/sqm:	170500
Average Pile Height:	3.0+/-0.5mm
Total Height:	5.2+/-0.5mm
Pile Weight:	550g/sqm
Total Weight:	3250g/sqm
Tile Size:	50*50cm
Backing:	E+Bac (Bitumen Backing)
Approved Installation Method:	 Brick      Quarter-turn
Flammability:	ASTM E 645: $\geq 0.22$ watts/cm <sup>2</sup> Class II
Smoke Density:	ASTM E 662: $\leq 450$ DMC
Dimensional Stability	AACHEN: $\leq 0.2$ %
Tuft Bind:	ASTM D 1335: $\geq 8.0$ lbs
Delamination:	ASTM D 3936: $\geq 3.0$ lbc/in
Static Propensity	AATCC 134: $\leq 3.5$ kV
Colorfastness to Light	AATCC 16E: $\geq 4-5$
Colorfastness to Water	AATCC 107: $\geq 4-5$
Colorfastness to Crocking	AATCC 165: $\geq 4-5$



AATCC 16E  
 $\geq 4-5$



AATCC 107  
 $\geq 4-5$



AATCC 165  
 $\geq 4-5$




AATCC 134  
 $\leq 3.5$  kV



ASTM D 3936  
 $\geq 3.0$  lbc/in



ASTM D 1335  
 $\geq 8.0$  lbs



AACHEN  
 $\leq 0.2$  %



ASTM E 662  
 $\leq 450$  DMC



ASTM E 645  
 $\geq 0.22$  watts/cm<sup>2</sup>  
Class II