



# Specification Sheet

Product:	Skyline*
	
Fiber:	100% Polypropylene
Structure:	Loop pile: Multi-Level loop
Gauge:	1/12"
Stitches:	10 per inch
Tufts/sqm:	186000
Average Pile Height:	4.0+/-0.5mm
Total Height:	7.0+/-0.5mm
Pile Weight:	680g/sqm
Total Weight:	3430g/sqm
Tile Size:	50*50cm
Backing:	E+Bac (Bitumen Backing)
Approved Installation Method:	 <p>Brick      Quarter-turn      Monolithic</p>
Flammability:	ASTM E 645: $\geq 0.22$ watts/cm <sup>2</sup> Class II
Smoke Density:	ASTM E 662: $\leq 450$ DMC
Dimensional Stability	AACHEN: $\leq 0.2$ %
Tuft Bind:	ASTM D 1335: $\geq 8.0$ lbs
Delamination:	ASTM D 3936: $\geq 3.0$ lbc/in
Static Propensity	AATCC 134: $\leq 3.5$ kV
Colorfastness to Light	AATCC 16E: $\geq 4-5$
Colorfastness to Water	AATCC 107: $\geq 4-5$
Colorfastness to Crocking	AATCC 165: $\geq 4-5$

\*Manufacture by Voxflor Industrial Park Co., Ltd

